HP Z420 Workstation

Expand your power.













Performance you want. Value you need.

The HP Z420 gives you professional expandability in an accessible tool-free mini-tower form factor—all at a great price. With up to 8 discrete processing cores, the latest processing and I/O power from Intel®, and the latest graphics technology from leading graphics providers, the HP Z420 has the power you need to get the job done.

Designed with ease.

Enjoy the control that comes with being able to swap out parts or make upgrades on your own. The HP Z420 Workstation features a smart chassis that offers tool-less access to the inside, easy configurability and an optional optical bay handle for seamless deployment. And with optional liquid cooling designed to deliver whisper-quiet performance, the HP Z420 is built to make your work flow more smoothly.

Enjoy superb performance.

Achieve the highest performance available in a single-processer personal workstation. The HP Z420 Workstations offers your choice of Intel® Xeon® E5-1600 and E5-2600 series processors 1.2.3—with base clock frequencies of up to 3.6 GHz and the new Intel® C602 chipset. Delivering support for up to 8 cores of processing power, the HP Z420 never slows you down.

Build it your way.

Build the HP Z420 Workstation the way you want with multiple SATA and SAS RAID configuration options that support a wide range of high-performance, high capacity storage solutions. Always know you're a step ahead with 8 DIMM slots in 4-channel memory architecture, delivering up to 64GB of 1600 MHz memory.

HP Z420 Workstation

	Convertible minitower							
Available Operating Systems	Windows 8 Pro 64-bit Windows 8 中文版 64-bit Windows 8 Pro Downgrade to Windows 7 Professional 32-bit Windows 8 Pro Downgrade to Windows 7 Professional 64-bit Windows 7 Professional 32-bit* Windows 7 Professional 64-bit* Windows 7 Professional 64-bit* Windows 7 Ultimate 64-bit* HP Linux Installer Kit SUSE Linux Enterprise Desktop 11 (90 day license) Red Hat Enterprise Linux Desktop/Workstation (1 year paper license; no preinstalled OS)							
Available Processors ^{1,2,3,4}	Processor	GHz	Cache	Memory	Cores	Hyper-Threading	Intel® vPro™ Technology	Intel® Turbo Boost Technology
	Intel® Xeon® Processor E5-2687W	3.1	20 MB	1600 MHz	8	Υ	٧	3, 7
	Intel® Xeon® Processor E5-2665	2.4	20 MB	1600 MHz	8	Y	Y	4, 7
	Intel® Xeon® Processor E5-1660	3.3	15 MB	1600 MHz	6	Ϋ́	Ϋ́	3, 6
	Intel® Xeon® Processor E5-1650	3.2	12 MB	1600 MHz	6	Υ	Υ	3, 6
	Intel® Xeon® Processor E5-1620	3.6	10 MB	1600 MHz	4	Υ	Υ	2, 3
	Intel® Xeon® Processor E5-1607	3.0	10 MB	1066 MHz	4	N	Υ	N/A
	Intel® Xeon® Processor E5-1603	2.8	10 MB	1066 MHz	4	N	Υ	N/A
Chipset	Intel® C602 Chipset							
Memory ⁶	8 DIMM slots, Up to 64 GB ECC unbuffered DDR3 1600 MHz; 4 channels per CPU							
Drive Controllers	Integrated 6-channel SATA controller: 2 ports 6 Gb/s + 4 ports 3 Gb/s, RAID 0, 1, 5, 10 capable; Optional SAS controller: LSI 9212-4i 4-port SAS/SATA 6 Gb/s, RAID 0, 1, 10 capable							
Storage ^{7,8}	Up to (4) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2, 3 TB, 12 TB max; Up to (4) 2.5-inch 10K rpm SATA drives: 250, 500 GB, 1 TB, 4 TB max; Up to (4) 2.5-inch 10K rpm SAS drives: 300, 600 GB, 2.4 TB max; Up to (4) 3.5-inch 15K rpm SAS drives: 300, 600 GB, 2.4 TB max; Up to (4) 2.5-inch SATA solid state drives: 128, 160, 256, 300 GB, 1.2 TB max. Note: Fourth 3.5-inch drive occupies one external 5.25-inch bay. Fourth 2.5-inch drive is installed into top optical bay handle.							
Optical Storage ^{9,10}	DVD-ROM, DVD+/-RW DL Super-Multi, Blu-ray Writer, 22-in-1 Media Card Reader							
Drive Bays	3 external 5.25-inch bays, 3 internal 3.5-inch HDD bays (4 total when using 5.25-inch bay converters); up to 4 eSATA							
	2 PCI Express Gen3 x16 mechanical/electrical; 1 PCI Express Gen3 x8 mechanical/electrical; 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 PCI Express Gen2 x4 mechanical/x1 electrical; 1 Legacy PCI							
Expansion Slots					Lnanical/ele	etticut, 11 et Express	delle vo mechanicatyva etec	trical;
Expansion Slots Available Graphics	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30(Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro	1 electrica), NVIDIA N 410, NVID 2000, NVII 4000, NVII	l; 1 Legacy IVS 310, NV IA Quadro K DIA Quadro	PCI 'IDIA NVS 510 '600, NVIDIA Qu K2000	adro 600, <i>F</i>	AMD FirePro™ V3900	00, NVIDIA Quadro K5000, N	
	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30(Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro High-end 3D: NVIDIA Quadro	1 electrica), NVIDIA N 410, NVID 2000, NVII 4000, NVII	l; 1 Legacy IVS 310, NV IA Quadro K DIA Quadro DIA Quadro	PCI /IDIA NVS 510 (600, NVIDIA Qu K2000 K4000, AMD Fir	adro 600, <i>F</i> ePro™ V790	AMD FirePro™ V3900 DO, AMD FirePro™ W70	00, NVIDIA Quadro K5000, N'	
Available Graphics	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30(Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro High-end 3D: NVIDIA Quadro NVIDIA Tesla Ca	1 electrica 0, NVIDIA N 410, NVID 2000, NVII 4000, NVII 075 Audio; Cre	l; 1 Legacy IVS 310, NV IA Quadro K DIA Quadro DIA Quadro ative Recon	PCI VIDIA NVS 510 (600, NVIDIA QU K2000 K4000, AMD Fir (3D PCIe Audio ()) dcom NIC; Optic	adro 600, <i>f</i> ePro™ V790 Card; option	AMD FirePro™ V3900 D0, AMD FirePro™ W70 nal HP Thin USB Power	00, NVIDIA Quadro K5000, N' red Speakers	VIDIA Quadro 6000,
Available Graphics	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30t Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro High-end 3D: NVIDIA Quadro NVIDIA Tesla Cz Integrated Intel/Realtek HD ALC262 Integrated Intel GbE LAN; Optional In HP 10GbE SFP+ SR Transceiver; Infir Front: 2 USB 3.0, 1 USB 2.0, 1	1 electrica), NVIDIA N 410, NVID 2000, NVII 4000, NVII 1075 Audio; Cre tel NIC; Open TPM IEEE 1394 IEEE 1394 igabit LAN	I; 1 Legacy IVS 310, NV IA Quadro K DIA Quadro DIA Quadro ative Recon tional Broa I.2 Controlle a standard I, 1 serial via	PCI PIDIA NVS 510 PIDIA NVS 510 PIDIA QU PIDIA Q	adro 600, A ePro™ V790 Card; option onal HP 361 in, 1 headp ports via o	AMD FirePro™ V3900 DO, AMD FirePro™ W70 Bal HP Thin USB Power IT PCle Dual Port Giga Ishone out, HP 22-in-1 ptional add-in PCle ca	00, NVIDIA Quadro K5000, N red Speakers bit NIC; Optional HP X520 10 Media Card Reader (optional rd, 1 audio in, 1 audio out, 1 i	VIDIA Quadro 6000, GbE Dual Port Adapter; Optional
Available Graphics Audio Network Ports	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30t Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro NVIDIA Quadro NVIDIA Tesla Ca Integrated Intel/Realtek HD ALC262 Integrated Intel GbE LAN; Optional In HP 10GbE SFP+ SR Transceiver; Infir Front: 2 USB 3.0, 1 USB 2.0, 1 Rear: 2 USB 3.0, 4 USB 2.0, 1 I RJ-45 to integrated 0	1 electrica), NVIDIA N 410, NVID 2000, NVII 4000, NVII 1075 Audio; Cre tel NIC; Open TPM IEEE 1394 IEEE 1394 igabit LAN to three H ard keyboa	I; 1 Legacy IVS 310, NV IA Quadro K DIA Quadro DIA Quadro ative Recon tional Broa 1.2 Controlle 1a standard 1, 1 serial via IP Internal L ard; USB Sm	PCI PIDIA NVS 510 600, NVIDIA QU K2000 K4000, AMD Fir BD PCIe Audio (dcom NIC; Optice er 1, 1 microphone 1, 2 IEEE 1394b a optional adap JSB Port Kits (o lart Card Keybo	adro 600, A ePro™ V790 Card; option onal HP 361 in, 1 headp ports via o ter ne two-por	AMD FirePro™ V3900 D0, AMD FirePro™ W70 nal HP Thin USB Power IT PCle Dual Port Giga Ihone out, HP 22-in-1 ptional add-in PCle ca t kit on each 2x5 head	00, NVIDIA Quadro K5000, N' red Speakers bit NIC; Optional HP X520 10 Media Card Reader (optional rd, 1 audio in, 1 audio out, 1 r ler)	VIDIA Quadro 6000, GbE Dual Port Adapter; Optional) microphone in, 2 PS/2,
Available Graphics Audio Network Ports	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30(Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro NVIDIA Quadro NVIDIA Tesla C2 Integrated Intel/Realtek HD ALC262 Integrated Intel GbE LAN; Optional In HP 10GbE SFP+ SR Transceiver; Infir Front: 2 USB 3.0, 1 USB 2.0, 1 Rear: 2 USB 3.0, 4 USB 2.0, 1 1 RJ-45 to integrated C Internal: 6 USB 2.0, supports up PS/2 standard keyboard; USB standard	1 electrica), NVIDIA N 410, NVID 2000, NVII 4000, NVII 0075 Audio; Cre tel NIC; Or eon TPM IEEE 1394 igabit LAN to three H ard keyboa USB Laser	I; 1 Legacy IVS 310, NVA A Quadro K DIA Quadro C DIA Quadro DIA Quadro DIA Quadro ative Recon tional Broa 1.2 Controlle la standard la standard 1, 1 Serial via P Internal L ard; USB Sm Scroll Mou	PCI PIDIA NVS 510 600, NVIDIA QU K2000 K4000, AMD Fir BD PCIe Audio (dcom NIC; Optice er 1, 1 microphone 1, 2 IEEE 1394b a optional adap JSB Port Kits (o lart Card Keybo	adro 600, A ePro™ V790 Card; option onal HP 361 in, 1 headp ports via o ter ne two-por	AMD FirePro™ V3900 D0, AMD FirePro™ W70 nal HP Thin USB Power IT PCle Dual Port Giga Ihone out, HP 22-in-1 ptional add-in PCle ca t kit on each 2x5 head	00, NVIDIA Quadro K5000, N' red Speakers bit NIC; Optional HP X520 10 Media Card Reader (optional rd, 1 audio in, 1 audio out, 1 r ler)	VIDIA Quadro 6000, GbE Dual Port Adapter; Optional) microphone in, 2 PS/2,
Available Graphics Audio Network Ports Input Devices	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30(Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro NVIDIA Quadro NVIDIA Tesla C2 Integrated Intel/Realtek HD ALC262 Integrated Intel GbE LAN; Optional In HP 10GbE SFP+ SR Transceiver; Infir Front: 2 USB 3.0, 1 USB 2.0, 1 Rear: 2 USB 3.0, 4 USB 2.0, 1 1 RJ-45 to integrated C Internal: 6 USB 2.0, supports up PS/2 standard keyboard; USB SpacePilot;	1 electrica), NVIDIA N 410, NVID 2000, NVII 4000, NVII 4000, NVII 7075 Audio; Cre tel NIC; Or tel NIC; Or tel Signature igabit LAN to three H ard keyboa USB Laser x 44.52 Cr	I; 1 Legacy IVS 310, NVA A Quadro K DIA Quadro C DIA Quadro DIA Quadro DIA Quadro ative Recon tional Broa 1.2 Controlle la standard la standard 1, 1 Serial via P Internal L ard; USB Sm Scroll Mou	PCI PIDIA NVS 510 600, NVIDIA QU K2000 K4000, AMD Fir BD PCIe Audio (dcom NIC; Optice er 1, 1 microphone 1, 2 IEEE 1394b a optional adap JSB Port Kits (o lart Card Keybo	adro 600, A ePro™ V790 Card; option onal HP 361 in, 1 headp ports via o ter ne two-por	AMD FirePro™ V3900 D0, AMD FirePro™ W70 nal HP Thin USB Power IT PCle Dual Port Giga Ihone out, HP 22-in-1 ptional add-in PCle ca t kit on each 2x5 head	00, NVIDIA Quadro K5000, N' red Speakers bit NIC; Optional HP X520 10 Media Card Reader (optional rd, 1 audio in, 1 audio out, 1 r ler)	VIDIA Quadro 6000, GbE Dual Port Adapter; Optional) microphone in, 2 PS/2,
Available Graphics Audio Network Ports Input Devices Dimensions (H x W x D)	1 PCI Express Gen2 x4 mechanical/x Professional 2D: NVIDIA NVS 30(Entry 3D: NVIDIA Quadro Mid-range 3D: NVIDIA Quadro NVIDIA Quadro NVIDIA Tesla C2 Integrated Intel/Realtek HD ALC262 Integrated Intel GbE LAN; Optional In HP 10GbE SFP+ SR Transceiver; Infir Front: 2 USB 3.0, 1 USB 2.0, 1 Rear: 2 USB 3.0, 4 USB 2.0, 1 1 RJ-45 to integrated C Internal: 6 USB 2.0, supports up PS/2 standard keyboard; USB spacePilot; 17.63 x 7.0 x 17.5 in (44.76 x 17.78)	1 electrica), NVIDIA N 410, NVIDIA N 410, NVID 2000, NVII 4000, NVII 6075 Audio; Cre tel NIC; Op eon TPM IEEE 1394 IEEE 1394 IEEE 1394 IEEE 1394 IEEE 1394 IEEE 1394 IEEE 1395	I; 1 Legacy IVS 310, NV IA Quadro K DIA Quadro C DIA Quadro DIA Quadro DIA Quadro ative Recon titional Broa 1.2 Controlle Ia standard Ia standard Ia standard In ternal L Ird; USB Sm Scroll Mou: n)	PCI PIDIA NVS 510 1600, NVIDIA Qu K2000 K4000, AMD Fir PIDIA PCIE Audio (RECONTROLLA PORTO RECONTROLL	adro 600, # ePro™ V79(Card; option onal HP 361 in, 1 headp ports via o tee tee two-port ard; PS/2 options.	AMD FirePro™ V3900 D0, AMD FirePro™ W70 D0, AMD FirePro™ W70 D1 HP Thin USB Power T PCIe Dual Port Giga Shone out, HP 22-in-1 ptional add-in PCIe ca t kit on each 2x5 head ptical scroll mouse; US	oo, NVIDIA Quadro K5000, N' red Speakers bit NIC; Optional HP X520 10 Media Card Reader (optional rd, 1 audio in, 1 audio out, 1 r ler) SB 2-button optical scroll mo	VIDIA Quadro 6000, GbE Dual Port Adapter; Optional) microphone in, 2 PS/2, use; USB 3-button optical mouse inch LED Backlit IPS Monitor, HP

Screen images courtesy of Autodesk

- This system may require upgraded and/or separately purchased hardware and/or a DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality windows-7/ for details.
- Multi-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits; Not all customers or software applications will necessarily benefit from use of these technologies.
 64-bit computing on Intel* architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel* 64 architecture. Processors will not operate
- (including 32-bit operation) without an Intel® 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See intel.com/info/em64t for more information. Intel®s numbering is not a measurement of higher performance.

 Although the Intel Xeon E5-2600 processor family supports dual processors, the HP Z420 Workstation does not support dual processor configurations.
- Actioning in the intervent E3-2000 processor affiling supports dual processors, tile in P2420 workstanding on the processor completed in the processor with lintel "Turbo Boost tepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A. Intel "Turbo Boost tepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A. Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. Processor with Intel "Turbo Boost tepping occurs in 100MHz increments. P

- For hard drives, 1 GB = 1 billion bytes. Actual formatted capacity is less.

 Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses.

 Note that DVD-RAM cannot read or write to 2.6 GB Single Sided/5.2 GB Double Sided de Version 1.0 media.

 As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD DVD movies cannot be played on this workstation.

 HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services and proposed interest the product product and proposed starts from fate of hardware purchases. To choose the right level of service for your HP product, use the HP Care Pack Services and proposed starts from fate of hardware purchases. To choose the right level of service for your HP product, use the HP Care Pack Services produces the product of the pr (go/lookuptool. Additional HP Care Pack Services information by product is available at hp.com/go/carepack. Service levels and response times for HP Care Packs may vary depending on your Lookup Tool at hp.com.

Learn more

hp.com/go/z420

© 2012-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Xeon, Core and vPro are trademarks of Intel Corporation in the U.S. and other countries. AMD is a trademark of Advanced Micro Devices, Inc. All other trademarks are the property of their respective owners.

